

# BUY 1 TRADESMAN<sup>®</sup> PRO HARNESSES PLUS 1 CTX<sup>™</sup> SRL-P

MIX & MATCH PROMOTION  
IS ONLY VALID FOR ITEMS  
SHOWN ON THIS PAGE.

MIX & MATCH  
GET  
**\$75 OFF**

## TRADESMAN<sup>®</sup> PRO



**7078C**  
Tradesman<sup>®</sup> Pro 3D Construction  
Belted Full Body Harness,  
Tongue Buckle Leg Adjustments



**7008C**  
Tradesman<sup>®</sup> Pro 1D Standard  
Non-belted Full Body Harness,  
Tongue Buckle Leg Adjustments

**BELTED**

SM-3X AVAILABLE AT TOTAL TOOL

**NON-BELTED**

SM-3X AVAILABLE AT TOTAL TOOL

Protection, plus comfort, the Tradesman<sup>®</sup> Pro harness is professional level at a price anyone can afford.

- V-slot locking D-ring plate minimizes slippage for maximum comfort and minimal adjustment throughout the day.
- Dorsal attachment tunnel allows for fast, hassle-free connection of single or twin SRL-Ps and keeps them optimally positioned on the back, reducing fatigue.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment.
- Tongue buckle legs provide quick lower-body adjustment.

## CTX<sup>™</sup> SRL-P



**83208TP1 SRL**  
8' CTX<sup>™</sup> Cable  
Class 2 Leading  
Edge Personal  
SRL-P, Twin-leg  
with Steel  
Snap Hooks

AVAILABLE AT  
TOTAL TOOL



**83208TP3 SRL**  
8' CTX<sup>™</sup> Cable  
Class 2 Leading  
Edge Personal  
SRL-P, Twin-leg  
with Steel  
Rebar Hooks

AVAILABLE AT  
TOTAL TOOL

The 8' CTX is a lightweight Class 2 personal SRL-P designed to provide all-day comfort and reduce fatigue.

- Includes all the quality and performance you demand at an easily accessible price.
- Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards, including steel and precast concrete.
- Rated for workers weighing up to 310 pounds, including clothes, tools, gear, etc.



SCAN HERE  
TO SHOP  
FALLTECH  
NOW

# SRD TYPES & CLASSES

Class 1 devices are suitable for at or above dorsal D-ring anchorage locations. Class 2 devices are suitable for above, at, or up to 5 feet below the dorsal D-ring anchorage locations AND must be leading edge rated. So, if you or your customer's jobsite has edge exposures and you need a leading edge SRL or SRL-LE, you will be looking for a Class 2 device in compliance with ANSI/ASSP Z359.14-2021! Coincidentally with the type and class changes, Z359.14-2021 also introduced standard overhead performance criteria for all SRDs as well as standardized class labeling. Now a worker can quickly identify the correct device for the hazards faced in their work zone.

In both the 2012 and 2014 revisions of Z359.14, overhead performance criteria was defined by SRD class: Class A or Class B. In 2021, overhead performance was standardized across all SRDs. The performance requirements are summarized in the table at right:

	"OLD" ANSI/ASSP Z359.14-2014		"NEW" ANSI/ASSP Z359.14-2021
SRD CLASS	CLASS A	CLASS B	CLASS 1 & CLASS 2
MAXIMUM ARREST FORCE	1,800 POUNDS		1,800 POUNDS
AVERAGE ARREST FORCE*	1,350 POUNDS*	900 POUNDS*	1,350 POUNDS*
MAXIMUM ARREST DISTANCE	24 INCHES	54 INCHES	42 INCHES

\*Note: During hot, cold and wet conditioned tests, average arrest force limit is increased.

# STANDARDIZED LABELING

All ANSI/ASSP Z359.14-2021 compliant SRDs will have one of the markings below consistent with its class:

In addition to the Class 1 and Class 2 standard labels, all Class 2 SRLs must include a full fall clearance table or diagram on the physical product, not just in the user instruction manual. This places critical fall-clearance information directly on the product, where it is most easily accessible by the end user or Competent Person.



DENVER, COLORADO  
303.595.8488

GREELEY, COLORADO  
970.352.8585

INDIANAPOLIS, INDIANA  
317.876.8800

DES MOINES, IOWA  
515.244.1516

KANSAS CITY, KANSAS  
913.722.7879

LOUISVILLE, KENTUCKY  
502.635.6348

HIBBING, MINNESOTA  
218.263.8687

ST. PAUL, MINNESOTA  
651.646.4055

LINCOLN, NEBRASKA  
402.476.6673

OMAHA, NEBRASKA  
402.592.7385

APPLETON, WISCONSIN  
920.687.4061

MILWAUKEE, WISCONSIN  
262.547.5548

SUPERIOR, WISCONSIN  
715.392.2294

WAUSAU, WISCONSIN  
715.848.2703

